

GPE XS

GPE SERIES "XS" ELECTRONIC RETAIL SHOP SCALES



Stainless steel retail scales, perfect for using in shop and working by battery. Printer protected under the plate from impacts and water.

FEATURES

- Dual alphanumeric backlight white LCD display, operator and client side. The backlight function can be removed.
- Double waterproof keyboard consists of 27 membrane keys plu / functions easily customizable thanks to the special side pocket and 35 mechan
- Thermal printer speed of 80mm/sec for normal thermal paper with paper 57mm wide, and outer diameter max. 50mm. Print width of up to 48mm.
- System for easily loading the paper. Print function of the logo.
- Stainless steel body, dimensions 360x235x500mm (LxWxH).
- Stainless steel plate, 360x235mm (LxW) size.
- 230Vac power supply with long-lasting built-in rechargeable battery.

FUNCTIONS


- Database of 3000 PLU's, 48 with direct access.
- 50 PLU groups.
- 600 ingredient lists.
- 4 VAT rates.
- 10 advertisement messages.
- · Queue-system.
- 8 payment modes.
- 2 kinds of short and long term totals.
- 4/8 operators.
- 3 programmable password levels.
- Operation mode: PLU priority, single item, multi-operator tickets.
- Weighing tare, operator tare, PLU tare, pre-stored and configurable tare.
- Reopening of the last operator ticket, discounts, rebates, cash management, customer management.

I/O SECTIONS

- 2 RS232 interfaces for connection to PC, modem, scanner, Helmac cash register.
- RS485 interface for connection with up to 4 scales in a local network.

INFORMATION

Available upon request





Approval:

DETAIL 1



New Keyboard Mechanics, for the operational part and membrane for PLU, easily customizable thanks to the convenient pocket





FOR RETAIL SOLUTIONS



www.helmac.com



HEAD OFFICE

Via della Fisica, 18 41042 Spezzano di Fiorano (MO) • Italy Tel.: +39 0536 070960

WAREHOUSE

Via della Fisica, 15 41042 Spezzano di Fiorano (MO) • Italy

| SALES | AND | TECHN | VICAL | ASSIS | TANCE | SERV | ICE |
|-------|-----|-------|-------|-------|-------|------|-----|